

Item Number:

**13248**

## Single-Use Roof Anchor

**Features:**

- For temporary anchorage on a roof peak structure
- Installs with (8) 3 1/2" 16d VC sinkers (included)
- Alloy steel construction
- Meets the requirements of OSHA 1926

**Material Specifications**

|              |                                             |
|--------------|---------------------------------------------|
| Roof Anchor: | Alloy steel; Min 3,600 lb. tensile strength |
|--------------|---------------------------------------------|

**Performance Specifications**

|                   |                 |
|-------------------|-----------------|
| Tensile Strength: | Min. 3,600 lbs. |
| Max. Capacity:    | 310 lbs.        |

**Relevant Standards**

|       |                           |
|-------|---------------------------|
| OSHA: | CFR 1926.502, CFR 1910.66 |
|-------|---------------------------|

**Warnings:**

- Read, understand, and follow all labels and instructions prior to use
- Inspect before each use
- Remove from service if there is evidence of damage or excessive wear



*Warning: this specification sheet provides an overview of products available from Northern Safety/FallTech. Care has been taken to assure the accuracy of the information. It does not provide important product warnings and instructions. Northern Safety/FallTech recommends all users of fall protection equipment undergo thorough training, and that all warnings and instructions provided with these products be thoroughly read and understood prior to use. Failure to read and follow all product warnings and instructions could result in serious injury or death.*