

Item Number:

23291

Hinged Self-Tracking Rope Grab

Features:

- Hinged design provides placement at any height along a vertical lifeline
- Dual locking threaded knob and safety latch
- Self-tracking design provides ease of vertical movement
- For use with 3' shock absorbing lanyard

Material Specifications

Ring/Body:	Alloy Steel; Min. 3,600 lbs. tensile strength
------------	---

Performance Specifications

Tensile Strength:	Min. 3,600 lbs.
Max. Capacity:	310 lbs.
Max. Freefall:	6 feet
Max. Arrest Force:	Less than 1,800 lbs.
Max. Elongation:	54 inches

Relevant Standards

OSHA:	CFR 1926.502, CFR 1910.66
ANSI:	Z359



Warnings:

- Read, understand, and follow all labels and instructions prior to use
- Inspect before each use
- Remove from service if there is evidence of damage or excessive wear
- Remove from service if there is any signs of activation
- Never attach a Shock Absorbing Lanyard to the front or side D-rings
- This product must be used in conjunction with a 3' shock-absorbing lanyard and rigged to allow a 6' max. freefall

Warning: this specification sheet provides an overview of products available from Northern Safety/FallTech. Care has been taken to assure the accuracy of the information. It does not provide important product warnings and instructions. Northern Safety/FallTech recommends all users of fall protection equipment undergo thorough training, and that all warnings and instructions provided with these products be thoroughly read and understood prior to use. Failure to read and follow all product warnings and instructions could result in serious injury or death.